

R290 Air Source Monoblock Heat Pump

Fuji air Catalogue





Eco-Smart Comfort: R290 Air Source Heat Pump

Fuji air R290 air source heat pump offers eco-friendly and energy-efficient heating and cooling solutions. Utilizing propane (R290) as the refrigerant, it ensures exceptional efficiency while reducing environmental impact. With its advanced technology, it achieves significant energy savings, making it a cost-effective choice for both residential and commercial spaces. The ultra-low Global Warming Potential (GWP) of 3 minimizes greenhouse gas emissions, contributing to a greener planet. Designed for silent operation and easy installation, it provides reliable and hassle-free comfort. Embrace the future of sustainable heating and cooling with our R290 air source heat pump, enjoying the eco-smart performance, energy savings, and superior comfort.



BLN-006|012 TC1
BLN-012 TC3



BLN-018 TC1
BLN-018 TC3






Hydro Tower

Fuji air Hydro Tower: the first choice for energy-efficient new builds

Modern heat pumps are among the most efficient and thus economical heating systems. With green electricity, their operation is absolutely climate-friendly. Not least for these reasons, most building owners today opt for a heat pump to heat their living spaces and to heat the water for bathing, showering and cooking. The new split-design heat pumps in the Fuji air Hydro Tower range are the first choice here, given that their refrigerant is also particularly climate-friendly.

Benefits of Hydro Tower

- Low operating costs due to high coefficient of performance
- Appealing, high-quality design of the internal and external unit
- Environmentally friendly refrigerant R290/R32.
- Reduced space requirements perfectly matched accessories for visually appealing installations
- Future-proof thanks to the most cutting-edge heat pump technology with natural refrigerant, reducing your carbon footprint
- Very quiet operation – can even be used in densely built-up terraced housing estates
- Outstanding quality and durability
- Choose from 200L or 250L Tank Options for Maximum Flexibility.
- Perfectly Compatible with Our R290/R32 Monoblock Heat Pump Solution.



Advantages of R290 Monoblock Heat Pump

DS

/D1



"Advantages of R290 Refrigerant: Eco-friendly "

R290 refrigerant offers numerous advantages. With a low Global Warming Potential (GWP) of 3, it significantly reduces environmental impact. It is energy efficient, safe, and reliable, making it an eco-friendly choice. R290 is also cost-effective, compatible with existing systems, and helps reduce carbon emissions, making it ideal for sustainable cooling and heating solutions.

/D2



"Silent Comfort: Serene Climate Control"

Our products offer a whisper-quiet operation, ensuring a serene environment. With advanced noise reduction technology, you can enjoy the perfect temperature without any disturbance. Experience tranquility at its best with our silent air source heat pumps.

/D3



"Effortless Installation: Simplify and Install"

Fujitsu air source heat pumps are designed with ease in mind, making installation a breeze. With simplified installation processes and user-friendly interfaces, you can have your system up and running in no time. Say goodbye to complicated setups and hello to hassle-free installation.

/04



“Freezing Conditions? No Problem!”

Fuji air air source heat pump thrives in frigid temperatures, operating flawlessly even at -25°C. Experience uninterrupted heating performance when you need it most. With our reliable technology, winter chills are no match for our resilient air source heat pump.

/07



“SG Ready”

Fuji air heat pump company proudly holds the SG Ready certification, developed by the German Heat Pump Association and 17 manufacturers. This seal confirms that our smart grid-capable heat pumps seamlessly communicate with "smart grids." Experience the benefits of utilizing surplus electricity for efficient heating, hot water, and mild summer cooling, ensuring an advantage in energy optimization and sustainability.

/05



"Smart Control at Your Fingertips"

With our cutting-edge air energy heat pump, you can experience the next level of smart heating and cooling. This system, which has integrated Internet of Things (IoT) technology, allows you to regulate and monitor the temperature of your house remotely. The 5" color screen has an intuitive interface for simple navigation and accurate temperature changes.

/08



"Versatile Comfort: Dual Temperature Zone"

The air source heat pump has a dual temperature zone, allowing you to adjust your living room floor heating to a comfortable 35°C and your room heater to a warm 55°C. With our novel dual temperature zone function, you may enjoy tailored comfort at its best.


/06



“Cut Costs, Conserve Energy”

The range of R290 air-to-water heat pumps is designed to deliver exceptional energy-saving benefits for heating and domestic hot water production. These pumps effectively harness the ambient air to transfer heat to the water system, resulting in reduced energy consumption and substantial cost savings. With our air-to-water heat pumps, you can enjoy eco-friendly and cost-effective heating solutions.

/09



“WIFI Module 5G/2.4G Compatible”

Stay connected with our innovative air energy heat pump, which includes a 5G/2.4G Compatible WIFI Module. Using your smartphone or tablet, you can operate and monitor your heat pump system from anywhere. For maximum comfort and energy efficiency, enjoy the simplicity of altering settings, scheduling temperature adjustments, and getting real-time notifications.

TECHNICAL DATA

Model		BLN-006TC1	BLN-012TC1	BLN-012TC3	BLN-018TC1	BLN-018TC3	
Power supply	V/Ph/Hz	220~240/1/50	220~240/1/50	380~415/3/50	220~240/1/50	380~415/3/50	
Nominal Heating (Max) (A7/6°C,W30/35°C)	Heating capacity	kW	2.92~9.1	4.30~15.20	4.30~15.20	7.24~22.1	7.24~22.1
	Power input	kW	0.61~2.11	0.87~3.73	0.87~3.73	1.5~5.88	1.5~5.88
	Current input	A	2.8~9.25	4.02~16.38	1.78~6.04	6.86~30.25	2.82~9.16
Nominal Heating (Max) (A7/6°C,W47/55°C)	Heating capacity	kW	2.99~8.16	4.25~14.55	4.25~14.55	6.36~19.45	6.36~19.45
	Power input	kW	1.03~2.92	1.45~4.28	1.45~4.28	2.15~6.85	2.15~6.85
	Current input	A	4.57~12.79	6.71~18.80	2.84~6.78	9.84~30.12	3.71~10.60
Nominal Cooling (Max) (A35/24°C,W12/7°C)	Cooling capacity	kW	1.38~5.70	3.65~11.4	3.65~11.4	4.55~17.20	4.55~17.20
	Power input	kW	0.67~2.44	1.12~3.97	1.12~3.97	1.85~7.31	1.85~7.31
	Current input	A	3.06~10.27	5.18~17.44	1.97~6.30	8.47~32.1	2.99~11.26
ERP level (outlet water temp. at 35°C)	/	A+++	A+++	A+++	A+++	A+++	
Max. input power	kW	3.50	5.40	5.85	7.50	10.50	
Max. input current	A	15.00	25.00	10.00	35.00	17.00	
Refrigerant	/	R290	R290	R290	R290	R290	
Rated water flow	m ³ /h	1.00	2.06	2.06	3.10	3.10	
Fan quantity	/	1	1	1	2	2	
Fan motor type	/	DC inverter					
Compressor	/	DC inverter					
Circulating pump	/	Inverter type / Built-in					
IP class	/	IPX4					
Sound pressure at 1m distance	dB(A)	42	50	50	55	55	
Max outlet water temperature	°C	75	75	75	75	75	
Water piping connections	/	DN 25 (1")	DN 25 (1")	DN 25 (1")	DN 32 (1-1/4")	DN 32 (1-1/4")	
Water Pressure drop(max)	kPa	20	20	20	55	55	
Operating temperature range (heating mode)	°C	-25~45					
Operating temperature range (cooling mode)	°C	16~45					
Unpacked dimensions (L*D*H)	mm	1187*418*805	1287*448*904	1287*448*904	1187*488*1456	1187*488*1456	
Packed dimensions (L*D*H)	mm	1217*463*920	1317*493*1020	1317*493*1020	1217*538*1570	1217*538*1570	
UnPacked weight	kg	110	123	123	184	184	
Packed weight	kg	115	128	128	192	192	

